

Gesellschaft für Internationale Zusammenarbeit GIZ

Greenhouse gas emissions from the transport sector: Mitigation options for Kenya Methodology and Results

Short report

Zurich, 22 November 2018

Benedikt Notter

Felix Weber

Jürg Füssler

Editorial Information

Greenhouse gas emissions from the transport sector:

Mitigation options for Kenya

Methodology and Results

Short report

Zurich, 22 November 2018

2616b01_Mitigation_Options_Kenya_Report_v4.docx

Commissioned by

Gesellschaft für Internationale Zusammenarbeit GIZ

Written by

Benedikt Notter

Felix Weber

Jürg Füssler

INFRAS, Binzstrasse 23, 8045 Zurich

Tel. +41 44 205 95 95

Advisory group

Urda Eichhorst, GIZ

Herman Kwoba, GIZ

Carol Mutiso, GIZ

Prof. Madara Ogot, University of Nairobi

Content

1.	Introduction	5
2.	Methodology	6
2.1.	General information valid for all four scenarios	6
2.1.1.	System boundaries and scope	6
2.1.2.	Modes and vehicle segmentation	7
2.1.3.	Emission factors	8
2.1.4.	Activity data	10
2.2.	Shift from road to rail	11
2.3.	Passenger vehicles efficiency	12
2.4.	Heavy goods vehicles efficiency	13
2.5.	Electrification	15
3.	Overview of results	16
4.	Discussion	18
	Literature	22
	Annex	24
A1.	Grid emission factors	24
A2.	NTSA body type classification and HBEFA segmentation	25

Glossary

BEV	Battery-electric vehicle
BRT	Bus Rapid Transit
CO ₂ e	CO ₂ equivalents
LCV	Light commercial vehicle
HGV	Heavy goods vehicle
GHG	Greenhouse gas
MC	Motorcycle
NCCAP	National Climate Change Action Plan (Kenya)
PC	Passenger car
PHEV	Plug-in hybrid electric vehicle
TTW	tank-to-wheel (emissions from combustion or use of fuel in vehicle)
WTT	well-to-tank (upstream emissions, e.g. from production and transportation of fuels)
WTW	well-to-wheel (total emissions, sum of TTW and WTT)

1. Introduction

The Kenyan government launched a revision process of its National Climate Change Action Plan (NCCAP, Government of Kenya 2013) in November 2017. The first NCCAP identified a number of priority mitigation actions for the transport sector (e.g. Bus Rapid Transit (BRT) and Light Rail Transit system implementation in Nairobi, passenger vehicle stock efficiency, improving HDV stock efficiency, bioethanol, biodiesel and shift of freight from road to rail). These actions need to be reviewed. With the TraCS project (Advancing Transport Climate Strategies), the Ministry of Transport, Infrastructure, Housing and Urban Development (MoTIHUD) in Kenya and the Deutsche Gesellschaft für Internationale Zusammenarbeit (GIZ) GmbH are developing a sectoral climate change strategy and a related accounting framework. The mitigation actions are one element of this strategy.

This project aims at recalculating the mitigation potential of four transport mitigation actions for Kenya (shift from road to rail, passenger vehicles efficiency, heavy goods vehicles efficiency, and electrification). BRT, which is assumed to have a high mitigation potential, is reviewed separately from the other actions due to its different system boundaries.

The report at hand includes information about the methodology used for the calculations and about important underlying assumptions for these calculations. Furthermore, it shortly discusses the results of the calculations. The detailed results are included in two separate Excel files, which use a different grid emission factor for electricity consumption:

- the first Excel calculation file includes the grid emission factor “Basic” (*“2616b01_Kenya_MitPot_Calc_gridEFbasic.xlsx”*),
- the second Excel calculation file includes the grid emission factor “Alternative” (*“2616b01_Kenya_MitPot_Calc_gridEFalternative.xlsx”*).

Both Excel files contain all the data used, the calculations with the equations, as well as figures and tables with results. A further, separate output is a PowerPoint file containing the resulting figures and tables (*2616b01_Kenya_MitPot_Results.pptx*).

2. Methodology

2.1. General information valid for all four scenarios

2.1.1. System boundaries and scope

Four scenarios were evaluated for Kenya's transport sector: (1) Shift from road to rail transportation; (2) Passenger vehicles efficiency; (3) Heavy goods vehicles efficiency and (4) Electrification. The following system boundaries are valid for all scenarios:

- **Temporal:** The base year for the analyses is 2015. Starting from the base year, the mitigation potentials are projected up to 2030 (in 5-year intervals).
- **Geographical:** The analyses reflect a national perspective. Accordingly, emissions are accounted for only if they occur within the national borders of Kenya. This particularly excludes upstream (well-to-tank, WTT) emissions of fossil fuels, i.e. the emissions from the production and transportation of fuels since these largely occur outside Kenya. For electricity on the other hand the upstream emissions of power generation are included in the scenario emissions, since the electricity is largely produced in Kenya itself. Thus, the results use the same assessment boundary as the national GHG inventory reporting (based on IPCC). This national perspective does therefore not reflect the full mitigation potential (reductions of WTT emissions from fossil fuels are not included). For this reason, the results on a global level (i.e. including WTT emissions from all fuels) are also provided in the Excel calculation file and in chapter 3 in order to show the difference between the national and the global perspective.
- **Transport sector:** The mitigation actions mainly aim at road transport (passenger cars, light commercial vehicles (LCV), buses and coaches, heavy goods vehicles (HGV) and motorcycles (MC)). However, the mitigation action on shift from road to rail also includes rail transport. An overview of the modes and vehicle segmentation considered in the analyses is shown in Chapter 2.1.2.
- **Greenhouse gases (GHG):** The results of the analyses reflect total GHG emissions in CO₂ equivalents (CO₂e).

2.1.2. Modes and vehicle segmentation

Table 1 shows the vehicle segmentation for road transport used in the analyses.

Table 1: Road transport (vehicle segmentation)¹

Vehicle category	Segments	Further information	Baseline / Scenario
Passenger cars (PC)	PC petrol < 1.4L	Size classes based on engine capacity in litres. Hybrid-electric vehicles (HEV; non-off-vehicle charging) are included here.	Both
	PC petrol 1.4 – 2L		Both
	PC petrol ≥ 2L		Both
	PC diesel < 1.4L		Both
	PC diesel 1.4 – 2L		Both
	PC diesel ≥ 2L		Both
	PC BEV	Battery electric vehicle	Scenario only
	PC PHEV (petrol)	Plug-in hybrid electric vehicle	Scenario only
Light commercial vehicles (LCV) ²	LCV petrol M+N1-I	Empty weight < 1305 kg	Both
	LCV petrol N1-II	Empty weight 1305 - 1760 kg	Both
	LCV petrol N1-III	Empty weight > 1760 kg	Both
	LCV diesel M+N1-I	Empty weight < 1305 kg	Both
	LCV diesel N1-II	Empty weight 1305 - 1760 kg	Both
	LCV diesel N1-III	Empty weight > 1760 kg	Both
	LCV BEV N1-II	Battery electric vehicle	Scenario only
Buses	Coach Std ≤ 18t (diesel)	Standard (med. size) bus/coach	Both
Heavy goods vehicles (HGV)	Rigid Truck < 7.5t (diesel)	Truck and trailer (TT) or articulated truck (AT)	Both
	Rigid Truck 7.5 – 12t (diesel)		Both
	Rigid Truck 12 – 14t (diesel)		Both
	Rigid Truck 14 – 20t (diesel)		Both
	Rigid Truck 20 – 26t (diesel)		Both
	TT/AT 20 – 28t (diesel)		Both
	TT/AT 28 – 34t (diesel)		Both
	TT/AT 34 – 40t (diesel)		Both
Motorcycles (MC)	MC 4S ≤ 150cc (petrol)	4-stroke engine	Both
	MC 4S 151 - 250cc (petrol)		Both
	MC 4S 151 - 250cc (petrol)		Both
	eScooter		Scenario only

Table INFRAS.

¹ Annex A2 shows how the NTSA body types are reflected by this segmentation.

² Class M: LCV for passenger transport with less than 6 seats and less than 2.5 tonnes empty weight
Class N1: LCV for passenger transport with more than 6 seats and more than 2.5 t empty weight or LCV for freight transport in three weight classes I-III (as listed under further information)

For the shift from road to rail, trains between Mombasa (port to international waterways), Nairobi (capital city) and Malaba (border to Uganda) were considered (see Table 2).

Table 2: Rail transportation (trains used)

Route	Trains	Further information	Baseline / Scenario
Mombasa (port) to Nairobi to Malaba (border to Uganda)	Electric passenger train	900 t gross weight, 2'622 kW locomotive (analogous to Chinese electric trains)	Scenario only
	Diesel passenger train	900 t gross weight, 3'610 kW locomotive	Scenario only
Mombasa (port) to Nairobi to Malaba (border to Uganda)	Electric freight train	4'000 t gross weight, 2'622 kW locomotive (analogous to Chinese electric trains)	Scenario only
	Diesel freight train	4'000 t gross weight, 3'680 kW locomotive	Scenario only

Table INFRAS.

2.1.3. Emission factors

Tank to wheel emission factors

The basis for estimating tank to wheel (TTW) emission factors for road transport in Kenya is the Handbook of Emission Factors for Road Transport (HBEFA Version 3.3, see INFRAS 2017a). The CO₂ emission factors for Kenya in the year 2015 were estimated in a separate pilot study (INFRAS 2018). In brief, a country-specific fleet composition and distribution of traffic situations for Kenya were derived and applied to the HBEFA base energy/fuel consumption and GHG emission factors (see INFRAS 2018 for technical and methodological details).

The CO₂ emission factors from HBEFA are transformed into CO₂ equivalent (CO₂e) emission factors by using the ratio between CO₂ and CO₂e from the EN 16258 standard (EU methodology for calculation and declaration of energy consumption and GHG emissions of transport services, see CEN 2012). These ratios (CO₂e per CO₂) amount to 102.45% for petrol and 101.64% for diesel. Accordingly, the results of the analyses reflect total GHG emissions in CO₂ equivalents.

The following assumptions were made for the development of the emission factors up to 2050 in the baseline:

- Regarding fuel efficiency development: The yearly reduction in fuel consumption of newly registered conventional (non-electric vehicles) is as follows (range of values indicate that the reduction is not linear over time):

- Light duty vehicles (PC and LCV): 1.2% reduction/a, based on optimization potentials of ICE engines and hybridization³ (SCCER Mobility 2017)
- HGV: 0.4 to 1.2% reduction/a of FC (based on ifeu and TUG 2015)
- Buses and MC: no reduction (since no information is available and it is assumed that there will not be legislation for buses and MC similar as is already in force or planned for PC, LCV and HGV e.g. in the European Union)
- The inputs regarding the fleet composition, and therefore the penetration of the efficiency of new vehicles in the entire vehicle fleet, are described in chapter 2.1.2.

The resulting average TTW emission factors for the baseline fleet in Kenya are show in Table 3.

Table 3: Tank-to-wheel (TTW) implied emission factors for road vehicle categories in the baseline

<i>in gCO₂e/km</i>	2015	2020	2025	2030	2035	2040	2045	2050
PC	189.6	170.0	151.1	137.9	128.4	120.5	113.5	107.1
LCV	220.2	213.1	205.5	195.3	184.4	173.9	164.0	154.6
Bus	860.1	864.8	866.2	866.6	866.7	866.7	866.7	866.7
HGV	772.3	742.5	708.0	671.7	637.0	608.1	589.0	574.7
MC	70.1	69.1	66.1	64.2	63.3	62.9	62.7	62.6

Table INFRAS. Source: INFRAS (2017a), INFRAS (2017b)

Well to tank emission factors

Well to tank (WTT) emission factors of fossil fuels are calculated according to the EN 16258 standard (CEN 2012) by using the ratio given between TTW and WTT emission factors by fuel type. The WTT emission factors amount to 19% of the TTW emission factors in the case of petrol and for 21% in the case of diesel.

Grid emission factors are used for **WTT emissions of electric vehicles** (i.e., BEV, PHEV, eScooters and electric powered trains). Two different versions of grid emission factors as shown in Table 4 were used in order to show how different assumptions regarding grid emission factors influence the mitigation potentials. For further information about the grid emission factors see Annex A1.

³ Example: fuel consumption in l/100 km of an average PC in Kenya in the year 2050 corresponds to that of a 2018 Toyota Prius.

Table 4: Grid emission factors used for electric powered vehicles

<i>in gCO_{2e}/MJ</i>	2015	2020	2025	2030	2035	2040	2045	2050
“Basic”: Grid EF from Kenya’s Second National Communication (Government of Kenya 2015)	33.4	96.1	104.6	103.2	90.3	89.3	88.6	87.9
“Alternative”: Grid EF from Least Cost Power Development Plan (LCPDP) Vision scenario⁴ (ERC 2018)	22.0	5.3	9.3	38.2	39.6	41.4	41.4	41.4

Table INFRAS. Source: Government of Kenya (2015) and ERC (2018)

2.1.4. Activity data

The following paragraphs describe the activity data (mainly vehicle-stock related information) relevant for the calculations in all four scenarios. The differentiation of the input data corresponds to the vehicle segmentation described in Chapter 2.1.2.

- Numbers of new registrations per year and vehicle category (see Table 6) were estimated by the University of Nairobi (Ogot et al. 2018, based on NCCAP in Government of Kenya 2013);
- Survival probabilities and age distributions of new registrations are based on Ogot et al. (2018). The age distributions of new registrations show that for PC and LCV, most newly registered vehicles are 8 or 9 years old, which corresponds well to the maximum import age of 8 years. For the other vehicle categories, most vehicles are newer at first registration in Kenya (less than 5 years old).
- The shares of the vehicle segments in new registrations within a given vehicle category are assumed equal to the shares in stock 2015/2016 (i.e. based on the petrol station survey carried out by Ogot et al. 2018, respectively with the modifications carried out in INFRAS 2018);
- The individual mileage per vehicle is assumed to remain constant from 2015 up to 2050 (there is no data or information available that suggests otherwise).

From the above inputs, the HBEFA fleet model calculated the fleet composition regarding number of vehicles and mileage shares, as well as total mileage of road transport.

Table 5: Projection of new registrations per year and vehicle category in Kenya

Baseline, number of vehicles	2015	2020	2025	2030	2035	2040	2045	2050
passenger cars	68'489	93'622	124'981	161'131	202'073	247'806	298'331	353'648
light commercial vehicles	23'878	18'016	23'471	29'836	37'113	45'300	54'397	64'406
buses	2'342	2'833	3'804	4'950	6'271	7'768	9'441	11'289
heavy goods vehicles	13'785	15'495	21'427	29'886	36'339	45'318	55'313	66'324
motorcycles	134'645	137'244	150'978	164'711	178'444	192'178	205'911	219'645

Table INFRAS. Source: Government of Kenya (2013), Ogot et al. (2018), estimated by University of Nairobi based on NCCAP.

⁴ Note that the update of the Least Cost Power Development Plan only includes data up to 2037. The grid EF was therefore kept constant between 2037 and 2050.

Additionally, population projections were used to derive the development of transport volumes in rail transport (Table 6).

Table 6: Projection of population development in Kenya

<i>In 1000 inhabitants</i>	2015	2020	2025	2030	2035	2040	2045	2050
Kenya national population	46'050	53'115	60'180	67'245	74'310	81'375	88'440	95'505

Data between 2015 and 2050 interpolated.

Table INFRAS. Source: United Nations (2015).

2.2. Shift from road to rail

The “shift from road to rail” scenario considers passenger cars, heavy goods vehicles and buses as well as diesel and electric trains on the route between Mombasa, Nairobi and Malaba (since relevant train lines only exist on this route).

Emission factors

The emission factors for road transport in the shift from road to rail scenario are identical as for the baseline. For rail transport, energy consumption of diesel and electric trains is based on EcoTransIT (2018), i.e. 10 Wh/Gtkm for electric and 27 Wh/Gtkm for diesel trains (both assumed to weigh 4000 t; see Table 7). The conversion factor from energy consumption to CO₂e emissions for diesel trains is based on Transphorm (2012) and takes the constant value of 720.6 g CO₂e/kWh.

For electric powered trains, the WTT (i.e. grid) emission factors were used as shown in Table 4.

Activity data

One main assumption in this scenario is that there is no rail transportation in the baseline⁵. The transport volumes between Mombasa – Nairobi and between Nairobi – Malaba for the year 2015 were extracted from the Transport Volumes Shapefile (KRB 2015) and projected according to population growth. It was assumed that the shift of passenger transport from road to rail will start from 2020 on (10% of passengers shifted) and reach 20% shift in passenger km from road to rail in 2050 (in between, the shift was linearly interpolated). The modal split in the shift from passenger cars and buses was estimated to be constant and equal to the modal split in the baseline in the year 2015 (11% of passenger km with passenger cars, 89% with bus). For freight transport, the capacity of rail freight is expected to reach 10'500 kt (22% of total

⁵ The old meter-gauge railway is ignored since it is not relevant in terms of transport volumes. The new Standard-gauge railway (SGR), although already in operation between Nairobi and Mombasa, is counted as a mitigation action.

capacity) in 2020 and 22'000 kt (35% of total capacity) in 2025, remaining constant after that until 2050 (in 2050: rail capacity amounts 16% of total capacity) (Kenya Railways 2018). It is assumed that 50% of the rail system will be electrified by 2050, starting from 0% in 2020 (linearly interpolated, assumption by the authors).

A shift from airplanes to road or rail transport was not included in the analyses.

Table 7: Important parameters for the shift from road to rail scenario (assumed constant for 2015-2050)

Parameter	Value	Source
Capacity of PC	5 persons per vehicle	Assumption by the authors
Occupancy of PC	2 persons per vehicle	Assumption by the authors
Capacity of buses	44 persons per vehicle	Research by GIZ Kenya
Occupancy rate of buses	60%	Assumption from the authors
Capacity of trucks	26 tonnes (for 40-t-trucks)	INFRAS 2017a
Average load of trucks	50%	EcoTransIt 2018
Capacity of passenger trains	1200 passengers	Kenya Railways 2018
Gross weight diesel passenger trains	900 tonnes	Research by GIZ Kenya
Gross weight electric passenger trains	900 tonnes	Assumption by the authors
Power diesel passenger trains	17.7 Wh/gross-tkm	EcoTransIt 2018
Power electric passenger trains	47.8 Wh/gross-tkm	EcoTransIt 2018
Occupancy of trains	703 passengers	Atkins 2018
Capacity of freight trains	2600 tonnes	Kenya Railways 2018
Average load of freight trains	54%	Kenya Railways 2018
Gross weight diesel freight trains	4000 tonnes	Kenya Railways 2018
Gross weight electric freight trains	4000 tonnes	Assumption by the authors
Power diesel freight trains	27 Wh/gross-tkm	EcoTransIt 2018
Power electric freight trains	10 Wh/gross-tkm	EcoTransIt 2018

Table INFRAS.

2.3. Passenger vehicles efficiency

The “passenger vehicles efficiency” scenario includes the road passenger vehicle fleets in the whole country.

Emission factors

The only change assumed in this scenario with respect to the baseline is that the maximum import age is lowered to 5 years (from 8 years as in the baseline). The age distributions of new registration were adapted accordingly.

Activity data

The activity data for the passenger vehicles efficiency scenario is mostly unchanged in comparison to the baseline. The only change in the scenario is that the maximum age of new registration vehicles is max. 5 years (100% of the new registrations) in comparison to the baseline, where the maximum import age is 8 years (see also Chapter 2.1.4).

The younger import age results in a longer duration of a vehicle being in use in Kenya until it is scrapped. For instance, if a vehicle was imported to Kenya at the age of 8 years and it was scrapped at the age of 30 years, it would be in use in Kenya for 22 years. In the scenario, the vehicle would be imported at the age of 5 years. The scrappage is assumed similar, i.e. at 30 years of age, and accordingly the vehicle is in use for 25 years.

If the other parameters (number of new registrations, annual mileage) were kept constant, the longer duration of a vehicle being in use in the scenario would lead to a higher total mileage of passenger vehicles in the scenario. This is not intended - the total mileage must be identical in baseline and scenario. Therefore, the individual annual mileage of the vehicles was lowered in the scenario in order to keep total mileage the same in the scenario and the baseline. Alternatively, the number of new registration per year could have been reduced (which may be the more likely effect, for instance due to higher average vehicle prices because they are imported at younger age). However, it does not matter for the calculated emissions which parameter is lowered. Reducing individual annual mileage was the more convenient approach, which is why this approach was chosen for adjusting the total mileage in the scenario.

2.4. Heavy goods vehicles efficiency

The “HGV efficiency” scenario includes HGV fleets in the whole country.

Emission factors

In the HGV efficiency scenario, the emission factors were changed compared to the baseline. Four effects were considered:

- Traffic density, congestion: it was assumed that the density of HGV traffic on rural roads and motorways is reduced due to infrastructure expansion. This was implemented by adapting the traffic situation distribution in HBEFA for these road categories in such a manner that all levels of service (LOS) except for free flow are changed to the next “lower” (i.e. less dense) level of service, i.e.:
 - “free flow” remains “free flow”
 - “heavy” becomes “free flow”
 - “saturated” becomes “heavy”
 - “stop + go” becomes “saturated”

This change in traffic situation distributions leads to a reduction in the TTW emission factor by 2.5% up to nearly 10% (depending on the year).

- Superstructures and tyres: in addition to the annual reduction of fuel consumption of new vehicles already assumed for the baseline emission factors (see Table 3), an additional efficiency gain was assumed due to improved superstructures (e.g. aerodynamics of superstructures), tyres (e.g. air pressure), and further effects.

These effects lead to 3.5 to 4% reduction of the emission factor.

- Road pavement: it was assumed that road roughness is reduced through better pavement conditions. Data on the International Roughness Index (IRI) was used from the Road Sector Investment Programme & Strategy (Government of Kenya 2010) for the years 2015 to 2024 (IRI 2015: 4.2, IRI 2024: 3.4). After that, it was assumed by the authors that IRI can be improved again in 2030 and will be constant from then on (IRI 2030-2050: 3.0). The effect of the IRI on the emission factor was estimated according to Memarian et al. (2014).

Through improved road pavements, the emission factor is reduced by 1.5 to 2.3%.

- Eco-Drive: it was assumed that eco-drive education for HGV drivers can reduce 10% of the fuel consumption (based on BFE 2007 and Hornung et al. 2001)⁶. It was further assumed that from the year 2020 on, the drivers of around 10'000 heavy goods vehicles could be reached through the education yearly and that the effect of the eco-drive education has an effect for 5 years.

This effect was estimated to lead to a 1% to 3.5% reduction of the emission factor.

Resulting from these efficiency assumptions, the following HGV TTW implied emission factors result for the HGV efficiency scenario:

Table 8: Tank-to-wheel (TTW) implied emission factors for the HGV efficiency scenario

<i>in gCO₂e/km</i>	2015	2020	2025	2030	2035	2040	2045	2050
HGV	708.7	674.6	629.4	597.8	568.8	539.1	509.8	481.6

Table INFRAS. Source: INFRAS (2017a), with data from Government of Kenya (2010), Memarian et al. (2014), BFE (2007), Hornung et al. (2001)

Activity data

For heavy goods vehicles efficiency, the activity data in the scenario is mostly unchanged compared to the baseline. Lowering the maximum import age does not have any effect since most HGV are imported at ages <5 years in the baseline already.

⁶ Studies find varying impacts of eco-drive: while BFE 2007 and Hornung et al. 2001 find impacts between 10-17%, Jeffreys et al. (2018) only find an impact of about 5%. The mean value of 10% was chosen for this analysis.

2.5. Electrification

For the “electrification” scenario, the entire fleet of road vehicle categories is included.

Emission factors

The emission factors for conventional road transport vehicles are identical as for the baseline. For electric vehicles, two different grid emission factors were used (see Table 4).

Activity data

The shares of battery electric vehicles (PC BEV and LCV BEV) and plug-in hybrid vehicles (PC PHEV) in new registrations are taken from a Swiss study (INFRAS 2017b) since no other data was available. However, an 8-year delay in the introduction of electric vehicles is assumed, since 8 years is the age of most imported vehicles in Kenya. This results in:

- PC: First electric vehicles in 2024, about 5.6% shares of BEV/PHEV (each) in new registrations by 2030, about 23.6% shares (each) in new registrations by 2050.
- LCV: First electric vehicles in 2024, about 2.3% share of BEV in new registrations by 2030, about 20% share in new registrations by 2050 (no PHEVs)
- The fuel efficiency development for the internal combustion engine of PHEVs is assumed similar as in Switzerland and taken from INFRAS (2017b). This was assumed because there is no other information available.

Furthermore, the following assumptions were made for the other electric vehicle categories:

- MC: Assumption of a very quick electrification of about half the fleet (using tax incentives as in the original introduction of bodabodas): Within 2015-2021, the share of e-Scooters in new registrations rises from 0% to 50%, then remains at the 50% level up to 2050.
- No CNG or fuel cell vehicles are assumed.

3. Overview of results

This section contains a short overview of the most important results (e.g. emission factors, mitigation potentials). More details can be found in the Excel and PowerPoint result files.

Emissions for the baseline and the scenarios are calculated by multiplying emission factors with activity data. The mitigation potential is calculated by subtracting the baseline emissions from the scenario emissions. The following table shows the mitigation potential results for the four scenarios. More detailed results are included in the Excel file, further figures can be found in the PowerPoint file.

Note that the different scenarios cannot be cumulated. The potentials of the different scenarios can be overlapping, because the measures (partially) target the same fleet. For instance: Kenya implements measures for both, a shift from road to rail passenger transport and a more efficient passenger vehicle fleet. According to our analysis for the mitigation action “passenger vehicle efficiency”, we assume that the whole fleet gets more efficient. The mitigation potential is the difference between the baseline and the scenario. However, if a specific share of the fleet is shifted to rail transport, there is no mitigation potential for this specific segment. The potential of the passenger vehicle efficiency can therefore not be fully exploited. Accordingly, if the potential of shift from road to rail and of passenger vehicle efficiency were cumulated, the total potential would be overestimated.

Table 9: Mitigation potential results for the four scenarios with the national perspective (grid EF «Basic»)

Scenario (national perspective)	unit	2015	2020	2025	2030	2035	2040	2045	2050	Total (2015-2050)	% of total BL
Shift road rail (grid EF "Basic")	Pot. kt CO ₂ e	-	-8	-33	-45	-64	-87	-122	-163	-2'197	-0.3%
	BL kt CO ₂ e	1'245	1'658	2'026	2'351	2'643	2'919	3'207	3'498	85'875	
Shift road rail (grid EF "Alternative")	Pot. kt CO ₂ e	-	-8	-42	-58	-79	-107	-147	-194	-2'686	-0.4%
	BL kt CO ₂ e	1'245	1'658	2'026	2'351	2'643	2'919	3'207	3'498	85'875	
Passenger vehicle efficiency	Pot. kt CO ₂ e	-	-117	-154	-159	-171	-188	-210	-235	-5'589	-0.8%
	BL kt CO ₂ e	4'080	5'694	6'874	8'225	9'773	11'476	13'295	15'197	324'884	
HGV efficiency	Pot. kt CO ₂ e	-233	-417	-691	-914	-1'117	-1'436	-2'054	-2'952	-41'106	-6.2%
	BL kt CO ₂ e	2'821	4'561	6'228	8'310	10'433	12'658	15'271	18'214	339'891	
Electrification (grid EF "Basic")	Pot. kt CO ₂ e	-	-6	-236	-560	-832	-1'025	-1'149	-1'214	-22'078	-3.3%
	BL kt CO ₂ e	6'901	10'255	13'102	16'535	20'206	24'134	28'566	33'411	664'775	
Electrification (grid EF "Alternative")	Pot. kt CO ₂ e	-	-6	-255	-629	-982	-1'344	-1'711	-2'072	-29'813	-4.5%
	BL kt CO ₂ e	6'901	10'255	13'102	16'535	20'206	24'134	28'566	33'411	664'775	
Total Kenya Road Transportation	BL kt CO ₂ e	6'901	10'255	13'102	16'535	20'206	24'134	28'566	33'411	664'775	

Legend: Pot. = mitigation potential; BL = baseline. Negative values indicate an emission reduction compared to the baseline, positive values an emission increase. Note that the baseline emissions are different for the four scenarios (different system boundaries for each scenario). Note that the shift from road to rail scenario also includes rail emissions, which are not included in the Total Kenya Road Transportation baseline (last row in table).

Table INFRAS.

Table 10 shows the same results as Table 9, but for the global instead of the national perspective. These results from the global perspective include all upstream emissions are in the mitigation potentials. Accordingly, the potentials are higher for the two scenarios “shift from road to rail” (due to an electrified rail system) and “electrification” (due to electric vehicles).

Table 10: Mitigation potential results for the four scenarios with the global perspective

Scenario (global perspective)	unit	2015	2020	2025	2030	2035	2040	2045	2050	Total (2015-2050)	% of total BL
Shift road rail (grid EF "Basic")	Pot. kt CO ₂ e	-	-9	-42	-58	-83	-113	-157	-210	-2'838	-0.4%
	BL kt CO ₂ e	1'509	2'010	2'456	2'850	3'204	3'540	3'890	4'242	104'125	
Shift road rail (grid EF "Alternative")	Pot. kt CO ₂ e	-	-9	-51	-71	-98	-133	-182	-241	-3'327	-0.5%
	BL kt CO ₂ e	1'509	2'010	2'456	2'850	3'204	3'540	3'890	4'242	104'125	
Passenger vehicle efficiency	Pot. kt CO ₂ e	-	-140	-184	-190	-204	-225	-250	-280	-6'664	-1.0%
	BL kt CO ₂ e	4'881	6'811	8'224	9'842	11'697	13'738	15'919	18'199	388'861	
HGV efficiency	Pot. kt CO ₂ e	-346	-608	-975	-1'290	-1'585	-2'018	-2'817	-3'958	-57'227	-8.6%
	BL kt CO ₂ e	3'423	5'534	7'557	10'084	12'660	15'359	18'530	22'102	412'432	
Electrification (grid EF "Basic")	Pot. kt CO ₂ e	-	-7	-285	-687	-1'041	-1'335	-1'573	-1'761	-29'040	-4.4%
	BL kt CO ₂ e	8'304	12'346	15'781	19'926	24'357	29'097	34'449	40'301	801'293	
Electrification (grid EF "Alternative")	Pot. kt CO ₂ e	-	-7	-303	-756	-1'191	-1'654	-2'134	-2'618	-36'775	-5.5%
	BL kt CO ₂ e	8'304	12'346	15'781	19'926	24'357	29'097	34'449	40'301	801'293	
Total Kenya Road Transportation	BL kt CO ₂ e	8'304	12'346	15'781	19'926	24'357	29'097	34'449	40'301	801'293	

Legend: Pot. = mitigation potential; BL = baseline. Negative values indicate an emission reduction compared to the baseline, positive values an emission increase. Note that the baseline emissions are different for the four scenarios (different system boundaries for each scenario). Note that the shift from road to rail scenario also includes rail emissions, which are not included in the Total Kenya Road Transportation baseline (last row in table).

Table INFRAS.

4. Discussion

Emissions from road transportation are expected to strongly increase by 2050.

The total vehicle km of road transport in Kenya increase exponentially between 2015 and 2050. The main reason for this increase is the increase of new registrations, which is developing in parallel with the projected population growth, along with constant mileage being assumed constant. This leads to a strong increase in emissions of road transportation by 2050, and consequently, to rising annual mitigation potentials up to 2050.

Due to the improvement in fuel efficiency in the countries of origin of the imported vehicles, the additional mitigation potential within Kenya is limited.

The increase in emissions is less pronounced than the increase in mileage due to improved fuel efficiency in the countries of origin of the vehicles imported to Kenya. A large share of the emission savings potential is already realized through this efficiency improvement, and these savings are included in the baseline. In turn, this means that less potential remains to be realized in Kenya itself. Improved road conditions, for instance, reduce emissions of a heavy goods vehicles by about 2% (see chp. 2.4). Accordingly, the more efficient new registered vehicles arrive in Kenya, the lower the absolute mitigation potential through this measure (improving road conditions) gets.

The highest potential lies in the efficiency of freight transportation.

The relevance of freight transport in Kenya is very high (in the baseline scenario, HGV account for 41% of total road transportation GHG emissions in 2015, for 50% in 2030 and for 55% in 2050). Thus, emissions from freight transport account for a large share of Kenya's road transport emissions already today. Therefore, measures not linked to the efficiency of the engine (like optimization of superstructures or tyres, reduced road roughness, eco-driving, etc.) can still have a major impact. In contrast, the efficiency improvements in passenger transportation are limited due to the improvements already realised in the countries of origin (which are included in the baseline), and due to the comparably minor to medium changes assumed in the scenarios "passenger vehicles efficiency" and "electrification".

From the national perspective (which only includes upstream emissions of fuels that are produced in Kenya), the potential of electric powered vehicles is medium.

For both mitigation activities, the shift from road to (partially electric) rail as well as the electrification, the high grid emission factor for upstream emissions reduces the potential. First, this is due to the electricity production mix. With the grid emission factor “Basic”, the mitigation action the mitigation potential is clearly lower as when the grid emission factor “Alternative” is used. The latter assumes much higher renewable shares in the electricity mix⁷. Second, the upstream emissions from electricity are included in the national perspective, whilst the upstream emissions from fossil fuels are not. The reduction of upstream fossil fuel emissions is not accounted for, while the increase of upstream electricity emissions is. Therefore, the potential of electrification is higher from the global than from the national perspective. Third, the assumed carbon intensity of the national grid is rather high and assumed to remain that high. A stronger impact of electrification can only be achieved in an integrative approach with a parallel de-carbonisation of the power sector.

From a global perspective, the reduction of upstream emissions of fossil fuels adds potential to electrification (in comparison to the national perspective)

The potential of the electrification mitigation option is about 20 to 30% higher when assessing it with the global perspective (i.e. with all upstream emissions) compared to the national perspective (i.e. only upstream emissions of electricity). The reason for this that from the national perspective, the reduction of upstream emissions for producing and transporting fossil fuels are outside the system boundaries and therefore not included. However, although the potential is clearly higher from the global perspective than from the national perspective, it is still rather small when compared to total road transportation emissions in Kenya. Mitigation actions would need to be considerably strengthened and de-carbonisation of national grid would be a requirement to achieve significant emissions reductions through electrification, as – to an extent – assumed in the grid emission factor “Alternative”. Accordingly, with this grid emission factor, the potential becomes more relevant and is the second-largest potential of the four mitigation actions assessed. One may assume that over the considered timeframe, many of the main countries that export vehicles to Kenya may undergo a shift from fossil to electric vehicles. Also, in line with the implementation of the Paris Agreement, it may be assumed that the Kenyan national grid will be de-carbonized so that electrification brings a higher mitigation impact than based on the assumptions of no climate action in this report.

⁷ Note that the grid emission factor «Alternative» drops in the year 2020 due to a complete and prompt phase-out of oil which is mainly compensated by electricity imports. See Annex A1 for more details.

The potential of a mode shift (road to rail) seems small.

The mitigation potential of a shift from road to rail is limited due to several reasons:

- High emission factor per pkm of diesel rail. A shift from bus to diesel train actually increases emissions (bus: 32-33 g/pkm TTW vs. diesel train: 44 g/pkm TTW, mainly due to occupancy rates).
- Only one train line in the whole country is assumed (apart from the BRT/LRT mitigation potential, which is not studied here).
- We had very little information on the planned capacity of the SGR. Its potential in terms of capacity may be higher than assumed here.

However, the potential of a shift from road to rail depends on when the rail system is electrified and what the carbon intensity of the electricity grid looks like (see discussion on electrification). Accordingly, the potential is higher when the grid emission factor “Alternative” is included in the analyses.

Uncertainties in the calculations of the mitigation potentials are rather high.

A lot of activity data was not readily available. Therefore, the authors were required to make assumptions on sensible parameters for the calculations or data with high uncertainty had to be used, for instance:

- Mode shift in the shift from road to rail scenario (in particular for the route between Nairobi and Malaba, where no rail transport is in place yet)
- Little information about the origin of HGV and about which efficiency improvements are achieved in Kenya and which in the countries of origin

Results in this report should therefore be interpreted with caution and readers are invited to consult the corresponding Excel file to further understand the assumptions taken.

Outlook:

- Given the high grid emission factors: What potentials to de-carbonise the power sector are there?
- Regarding electrification of the vehicle fleet, what is the chance for the Kenyan vehicle market to become more independent of vehicle imports from industrial countries? In the results presented, we assume the same development as conservatively expected in Japan or Europe, with an 8-year delay. However, the Kenyan fleet could potentially be electrified much faster, e.g. with direct imports of electric vehicles from China.
- Regarding efficiency improvements apart from electrification: Only one, not very drastic, measure is envisaged, i.e. reduction of the maximum import age from 8 to 5 years. One could also discuss a complete ban on used imported cars, which other countries (e.g. Latin-American or North African countries) have implemented already.
- Shift from road to rail: What is the envisaged capacity in terms of daily/annual passenger numbers of the SGR (see Table 11 for illustration)? Could it be feasible to envisage more ambitious goals in terms of mode shift – e.g. more train lines than just along this one corridor?

Table 11: Passenger kilometres in the shift from road to rail scenario (for SGR)

<i>In Mio. pkm</i>	2015	2020	2025	2030	2035	2040	2045	2050
Road	8'629	8'982	9'993	10'961	11'886	12'768	13'607	14'403
Rail	0	971	1'284	1'640	2'038	2'480	2'965	3'493

Table INFRAS.

Literature

- BFE Bundesamt für Umwelt (Federal Office of Energy) 2007:** Expertise «Wirkungsberechnung Eco-Drive». Berne.
- CEN European Committee for Standardization 2012:** CSN/TC 212; EN 16258:2012. Methodology for calculation and declaration of energy consumption and GHG emissions of transport services (freight and passengers). European Standard, Brussels, Belgium.
- EcoTransIT 2018:** Ecological Transport Information Tool for Worldwide Transports. Methodology and Data, Update 2018. Commissioned by EcoTransIT World Initiative (EWI). ifeu Heidelberg, INFRAS Berne, IVE Hannover.
- ERC Energy Regulatory Commission 2018:** Updated Least Cost Power Development Plan. Study Period: 2017-2037.
- Government of Kenya (2010):** Road Sector Investment Programme & Strategy 2010-2024. Ministry of Roads, Nairobi.
- Government of Kenya (2013):** National Climate Change Action Plan 2013-2017 (NCCAP). Ministry of Environment and Mineral Resources, Nairobi, Kenya.
- Government of Kenya (2015):** Kenya Second National Communication to the United Nations Framework Convention on Climate Change. Ministry of Environment and Mineral Resources, Nairobi, Kenya.
- Hornung, D., Röthlisberger, T. 2001:** Eco-Drive im Test. Evaluation der Eco-Drive Simulator-Kurse. Mandated by Quality Alliance Eco-Drive (QAED). Berne.
- ICCT 2015:** Policies to reduce fuel consumption, air pollution, and carbon emissions from vehicles in G20 nations. International Council on Clean Transportation (ICCT). [https://www.theicct.org/sites/default/files/publications/ICCT_G20-briefing-paper_Jun2015_updated.pdf].
- ifeu, TUG 2015:** Zukünftige Massnahmen zur Kraftstoffeinsparung und Treibhausgasminderung bei schweren Nutzfahrzeugen. Institut für Energie- und Umweltforschung (ifeu) und Technische Universität Graz (TUG). [https://www.umweltbundesamt.de/sites/default/files/medien/378/publikationen/texte_32_2015_kraftstoffeinsparung_bei_nutzfahrzeugen.pdf].
- IFEU 2016:** Aktualisierung „Daten- und Rechenmodell: Energieverbrauch und Schadstoffemissionen des motorisierten Verkehrs in Deutschland 1960- 2035“ (TREMODO) für die Emissionsberichterstattung. Im Auftrag des Umweltbundesamtes. Institut für Energie- und Umweltforschung (IFEU), Heidelberg. [https://www.ifeu.de/wp-content/uploads/Endbericht_TREMODO_2016_160701.pdf].
- INFRAS 2017b:** Handbook Emission Factors for Road Transport (HBEFA), Version HBEFA 3.3 (April 2017). INFRAS, Berne. [www.hbefa.net/]

- INFRAS 2017b:** Pilotstudie zum Treibstoffverbrauch und den Treibhausgasemissionen im Verkehr 1990-2050 - Szenarien für den Strassenverkehr. Schlussbericht. Bundesamt für Umwelt (BAFU), Bern. [<https://www.bafu.admin.ch/dam/bafu/de/dokumente/klima/fachinfoda-ten/Pilotstudie%20zum%20Treibstoffverbrauch%20und%20den%20Treibhausgasemissionen%20im%20Verkehr%201990-2050.pdf.download.pdf/pilotstudie-verkehr-1990-2050.pdf>].
- INFRAS 2018:** Road transport GHG emission factors for Kenya. Pilot study for 2015. Mandated by GIZ. INFRAS, Berne.
- Jeffreys, I., Graves, G., Roth, M. 2018:** Evaluation of eco-driving training for vehicle fuel use and emission reduction: A case study in Australia. *Transportation Research*, Vol. 60, pp. 85-91.
- Kenya Railways 2018:** Information about passenger and freight transport capacities up to 2025. Written communication to Herman Kwoba, GIZ Kenya.
- KRB 2015:** Road Traffic Module. Dataset from April 2015. Kenya Roads Board.
- Memarian, A., Zabihi, M., Ardekani, S.A., (2014):** A synthesis of roadway surface impact on GHG and PM10 emissions. *International Journal of Engineering & Technology*, Vol. 3(1), pp. 1274-1286.
- Ogot, M., Nyang'aya, J., Nkatha, R. 2018:** Characteristics of the in-service vehicle fleet in Kenya. Draft report V1. Commissioned by Deutsche Gesellschaft für Internationale Zusammenarbeit (GIZ). University of Nairobi, Nairobi.
- SCCER Mobility 2017:** Auf dem Weg zu einem energieeffizienten und klimafreundlichen Schweizer Mobilitätssystem. White Paper - September 2017. Swiss Competence Center for Energy Research: Efficient Technologies and Systems for Mobility (SCCER Mobility). [https://www.sccer-mobility.ch/export/sites/sccer-mobility/capacity-areas/dwn_capacity_areas/SCCER_Mobility_White_Paper_Sept2017.pdf].
- Transphorm 2012:** Transport related Air Pollution and Health impacts – Integrated Methodologies for Assessing Particulate Matter. Report on railway emission factors. Deliverable D1.2.5, type R of the Seventh Framework Programme.
- United Nations 2015:** World Population Prospects - the 2015 Revision. Key Findings and Advance Tables. New York.
- Yang, Z., Bandidavekar, A. 2017:** 2017 global update: Light-duty vehicle greenhouse gas and fuel economy standards. International Council on Clean Transportation (ICCT). [<https://www.theicct.org/publications/development-test-cycle-conversion-factors-among-worldwide-light-duty-vehicle-co2>].

Annex

A1. Grid emission factors

The electricity mix used for the **grid emission factor “Basic”** from Kenya’s Second National Communication (Government of Kenya 2015) is not publicly available. However, in the executive summary (p. 4) states that *“Hydropower, which constitutes over half of the total effective grid connected electricity, is highly vulnerable to variations in hydrology and climate. Poor rains result in hydroelectricity shortfalls, leading to more costly and GHG-intensive electricity generation through diesel. Geothermal accounts for 12.2 per cent of the electricity mix and the remaining 29.7 per cent is predominantly petroleum-based thermal generation. Kenya’s National Energy Policy 2014, which has been formulated within the framework of Vision 2030, encourages diversification of electricity sources, including addition of geothermal (1,646MW), natural gas (1,050MW), wind (630MW) and coal (1,920MW). This new plan, despite potentially increasing GHG emissions from coal, aims to improve energy security and reduce the recent trend of oil thermal comprising the largest portion of new capacity.”*

The electricity mix used for the **grid emission factor “Alternative”** from the LCPDP Vision scenario (ERC 2018) is shown in Table 12. The LCPDP Vision scenario assumes that by 2037, geothermal electricity generation will account for the largest share of production. Also, the scenario assumes that there is a complete and prompt phase out of oil in the year 2020. The electricity gap occurring from that would be covered by imports, which would not lead to emissions in the national perspective (because WTT emissions occurring abroad are not included in the national perspective and TTW emissions of electricity are assumed to be zero).

Table 12: Electricity mix for the grid emission factor “Alternative” (LCPDP Vision)

Technology	unit	2015	2020	2025	2030	2035	2037
Onshore Wind	Gwh	0.8%	12.3%	12.9%	10.9%	11.9%	10.3%
Offshore Wind	Gwh	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
Solar PV	Gwh	0.0%	2.9%	4.9%	3.9%	2.8%	2.5%
Biopower	Gwh	0.0%	1.5%	3.2%	2.8%	2.3%	2.1%
Hydro	Gwh	39.6%	24.1%	16.9%	16.1%	11.5%	10.2%
Geothermal	Gwh	52.3%	42.3%	50.1%	43.4%	50.9%	47.3%
Natural Gas	Gwh	0.0%	0.0%	0.0%	2.5%	2.3%	3.0%
Coal	Gwh	0.0%	0.0%	1.3%	12.7%	13.0%	13.6%
Oil	Gwh	7.3%	0.0%	0.0%	0.0%	0.0%	0.0%
Nuclear	Gwh	0.0%	0.0%	0.0%	0.0%	0.0%	6.3%
Solar Minigrid	Gwh	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
Wind Minigrid	Gwh	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
Diesel Minigrid	Gwh	0.0%	0.0%	0.0%	0.0%	0.0%	0.0%
Generic backup	Gwh	0.0%	0.0%	0.0%	0.0%	0.0%	0.1%
Import	Gwh	0.0%	16.9%	10.7%	7.8%	5.4%	4.7%
Total	Gwh	9'453	15'633	24'580	34'805	50'555	57'985

Table INFRAS. Source: ERC (2018)

A2. NTSA body type classification and HBEFA segmentation

Table 13: Assignment of NTSA body types to HBEFA vehicle types

Body type ID	NTSA Body type	HBEFA vehicle category	HBEFA segment ⁸ assignment
1	S.WAGON	Passenger car (PC)	based on engine capacity [l]
2	LORRY/TRUCK	Heavy goods vehicle (HGV)	based on max. weight [t]
3	PICKUP	Light commercial vehicle (LCV)	based on empty weight [t]
4	CRAWLER		
5	ROLLER/GRADER/CRANE/COMBINE HARVESTER		
6	Combine harvester	N/A (non-road mobile machinery)	
7	PRIME MOVER		
8	BACKHOE LOADER		
9	SPECIAL PURPOSE		
10	TRAILER	Not directly assigned, since trailers only circulate combined with a tractor. Considered via HBEFA “transformation pattern”, which specifies the percentage of tractor vehicles moving with trailer, by size class.	
11	M.BUS/MATATU	Light commercial vehicle (LCV)	based on empty weight [t]
12	MOTOR CYCLE	Motorcycle (MC)	
13	FORK LIFT	N/A (non-road mobile machinery)	
14	BUS/COACH	Coach	assumed standard size class (<=18 t max. weight)
15	COUPE	Passenger car (PC)	based on engine capacity [l]
16	TIPPER	Heavy goods vehicle (HGV)	based on max. weight [t]
17	THREE WHEELER	Neglected, since low population and no corresponding HBEFA vehicle type available	
18	WHEEL/TRACTOR	Heavy goods vehicle (HGV)	based on max. weight [t]
19	DOUBLE CAB	Light commercial vehicle (LCV)	based on empty weight [t]
20	VAN	Light commercial vehicle (LCV)	based on empty weight [t]
21	SALOON	Passenger car (PC)	based on engine capacity [l]
22	WHEEL LOADER		
23	Others	N/A (non-road mobile machinery)	

Table INFRAS. Source: University of Nairobi, own analysis